



CRAFTMATIC DEPOSITOR

The Craftmatic Depositor range has been designed to give the user high efficiencies, flexibility and reliability. The machines have a minimal number of components making hygiene strip down quick and easy. The units' large inlet and outlet ports ensure product degradation is minimised.

Weight control is simple and precise using the well proven 'T' bar screw adjustment system. The depositors come as either bench models or on mobile frames, allowing for maximum flexibility of location. Robustly built, the units are designed to withstand the rigours of everyday production.





CRAFTMATIC DEPOSITOR SPECIFICATION

- SPEED:** Up to 70 cycles per minute dependant on product specification.
- CAPACITY:** 310 gramme product cylinders and 38mm AP nozzle are fitted as standard.
- HOPPER:** 40 litre capacity is standard.
- SPARES:** Standard spares kits are obtainable from our Spares Department.
- CONSTRUCTION:** All stainless steel with food quality plastics and any aluminium components hard anodised.
- CONTROLS:** Controls are hand adjustable. Deposit weight and speed of operation are easily adjusted with depositor in motion or at rest. The depositor will accept a signal from existing equipment and will run continuously with adjustable cycle rate.
- ACCURACY:** The depositors are extremely accurate by volume and weight ranges within ± 2 grammes are normal.
- HYGIENE:** The depositor easily dismantles for hygiene and may be safely hosed.
- TECHNICAL DATA:** Compressed air supply 80 psi, 8-12 cfm per cycle. Fitted with 12mm filter pressure regulator.

OPTIONS

- Larger barrel and piston
- Larger hopper
- Foot switch signal
- 25mm diameter AP Nozzle
- 50mm diameter AP Nozzle
- 25mm diameter Sealing Nozzle
- 38mm diameter Sealing Nozzle
- 50mm diameter Sealing Nozzle
- Rise and Fall Heads by application
- Rotary Valves by application
- Screw Feed Level Control

